

SCG (THAILAND) CO.,LTD.



**F**ORKLIFT &  
**LIQUID WITHDRAWAL VALVES**

## FORKLIFT & LIQUID WITHDRAWAL VALVE



D-V6-CH

Model No. D-V6-CH  
 Safety Relief : Flow 5.1 M3/Min (26 BAR)  
 Bleeder Screw : Without  
 Inlet Thread : 25E (EN 629 - 1)  
 Outlet Thread : 1 - 1/4" - 5 ACME -2G - RH  
 Excess Flow Device : With  
 Ferrule : Without  
 Dip Tube : With  
 HandWheel : Brass



D-V6-X.10

Model No. D-V6-X.10 (FORKLIFT VALVE)  
 Safety Relief : Flow 450 CFM (375 PSI)  
 Bleeder Screw : Without  
 Inlet Thread : 3/4" - 14NGT  
 Outlet Thread : 1 - 1/4" - 5 ACME -2G - RH  
 Excess Flow Device : With  
 Ferrule : Without  
 Dip Tube : With  
 HandWheel : Brass



D-V6-Y

Model No. D-V6-Y  
 Safety Relief : Without  
 Bleeder Screw : Without  
 Inlet Thread : 3/4" - 14NGT  
 Outlet Thread : 1 - 1/4" - 5 ACME -2G - RH  
 Excess Flow Device : With Closed at Flow Capacity 5.4 L/Min LPG  
 Ferrule : Without  
 Dip Tube : With  
 HandWheel : Brass



D-V87-AL

Model No. D-V87-AL  
 Safety Relief : Flow 460 CFM (Air) (26 BAR)  
 Bleeder Screw : Without  
 Inlet Thread : 3/4" - 14NGT  
 Outlet Thread : 0.903" - 14 NGO - LH - INT (CGA 555)  
 Excess Flow Device : With Closing Flow Rate 6.5 L/Min (LPG)  
 Ferrule : Without  
 Dip Tube : With  
 HandWheel : Aluminium  
 Colour : RED

## FORKLIFT & LIQUID WITHDRAWAL VALVE



D-V87-AO

Model No. D-V87-AO  
 Safety Relief : Without  
 Bleeder Screw : Without  
 Inlet Thread : 3/4" - 14NGT  
 Outlet Thread : 0.885" - 14 NGO - LH - INT (CGA 510)  
 Excess Flow Device : With  
 Ferrule : Without  
 Dip Tube : With  
 HandWheel : Aluminium  
 Colour : RED



D-V87-AV

Model No. D-V87-AV  
 Safety Relief : Flow 460 CFM (Air) (25 BAR)  
 Bleeder Screw : Without  
 Inlet Thread : 3/4" - 14NGT  
 Outlet Thread : 0.885" - 14 NGO - LH - INT (CGA 510)  
 Excess Flow Device : With  
 Ferrule : Without  
 Dip Tube : With  
 HandWheel : Aluminium  
 Colour : RED



D-V8-C

Model No. D-V8-C (Dual Valve Liquid Offtake)  
 Safety Relief : With 375 - 480 PSI  
 Bleeder Screw : Without  
 Inlet Thread : 3/4" - 14 NGT  
 Outlet Thread : 0.885" - 14 NGO(VAPOUR)/ 3/8" - SAE Flare RH (Liquid)  
 Excess Flow Device : With  
 Ferrule : Without  
 Dip Tube : With  
 HandWheel : Aluminium  
 Colour : RED, BLACK



D-V5-AW

Model No. D-V5-AW (SERVICE VALVE For Forklift Cylinder)  
 Safety Relief : Without Bleeder Screw : Without  
 Inlet Thread : 3/4" - 14NGT Outlet Thread : 3/8" - 18 NPT  
 Excess Flow Device : With  
 Ferrule : Without  
 Dip tube : Without  
 HandWheel : Aluminium



D-M220M-A

Model No. D-M220M-A (ACME CONNECTOR)  
 Safety Relief : Without Bleeder Screw : Without  
 Inlet Thread : 1 1/4" - 5 ACME 2G RH Outlet Thread : 3/8" - 18 NPT RH  
 Excess Flow Device : Without  
 Ferrule : Without Dip Tube : Without  
 HandWheel : Without

## FORKLIFT & LIQUID WITHDRAWAL VALVE

<p>D-7545K-A</p>	 	<p>Model No. D-7545K-A (SAFETY RELIEF VALVE)                      Setting at 2.55 MPa Inlet Thread : 3/4" - 14 NGT                      Outlet Thread : M19 x 1.25 Female</p>
<p>D-ADAPT-D</p>	 	<p>Model No. D-ADAPT-D(FEMALE ACME ADAPTOR)                      Safety Relief : Without Bleeder Screw : Without                      Inlet Thread : 1 - 1/4" - 5ACME - 2G - RH Outlet Thread : 1/4" - 18 NPT                      Excess Flow Device : Without Ferrule : Without                      Dip Tube : Without HandWheel : Without                      Remark : Brass Female ACME Adaptor</p>
<p>D-W-A</p>	 	<p>Model No. D-WV-A (VENT OUTAGE VALVE/LIQUID LEVEL GAUGE)                      Inlet Thread : 1/4" - 18 NPT Nut HEX 14 MM.</p>
<p>D-FV-A</p>	 	<p>Model No. D-FV-A (FILLER VALVE)                      Safety Relief : Without Bleeder Screw : Without                      Inlet Thread : 3/4" - 14 NGT Outlet Thread : 1 3/4" - 6 ACME 2G                      Excess Flow Device : With                      Ferrule : Without Dip Tube : Without                      HandWheel : Without Remark : With Plastic Dust CAP</p>
<p>D-GAUGE-C</p>	 	<p>Model No. D-GAUGE-C (FLOAT GAUGE)                      Horizontal Typed Connection Thread : 3/4" - 14 NPT Float Arm Moving Angle 55o</p>
<p>D-GAUGE</p>		<p>Model No. D-GAUGE (LEVEL GAUGE)</p>
<p>D-W-A</p>	 	<p>Model No. D-WV-A (Vent Valve)                      Safety Relief : Without Bleeder Screw : Without                      Inlet Thread : 1/4" - 18NGT Outlet Thread : -Excess Flow Device : Without                      Ferrule : Without Diptube : With as required                      HandWheel : Without Remark : With Nameplate</p>

